



IP67 rating

The world's first dust and water proof system designed for harsh field conditions.



Multi-orientation handle

Detachable handle for portrait or landscape orientation.



"Hot-swappable" batteries

Two hot-swappable batteries for never-ending continuous operation in the field.



One-touch operation

2-3 second time-lapse for image capture.



Remote multi-screen control

Wireless operation up to one mile. Supports multi-screen control through any mobile device.



MIL-STD connectors

VEO v5.0




Xsight

One touch filter capability




External Camera

Combines image with external camera



Stitching

Automatic image stitching



Dual Energy

Differentiates organic and inorganic materials



Annotations

Annotations and image measurement options



Subtraction

Compares two images, while highlighting the differences

| System Specifications | Guardian 17 | Guardian 12 |
|-----------------------|--|--|
| Imaging area | 358 mm x 431 mm (-14" x 17") | 254 mm x 317 mm (~10" x 12") |
| Panel dimensions | 470 mm x 400 mm (~18.5" x 15.7") | 355 mm x 322 mm (~14" x 12") |
| Panel thickness | 17 mm (0.6") | 17mm (0.6") |
| IP rate | 67 | 67 |
| Pixel size | 140 μm | 124 µm |
| lp/mm | 3.5 | 4 |
| Panel bit | 16 bit | 16 bit |
| Panel dead space | 8 mm (portrait mode) 10 mm (landscape mode) | 8 mm (portrait mode), 8 mm (landscape mode) |
| Wireless | Up to 1.6 km (1 mile) line of sight | Up to 1.6 km (1 mile) line of sight |
| Operating time | Continuous "Hot-swappable" batteries | Continuous "Hot-swappable" batteries |
| Packaging | Rugged case; tactical backpack | Rugged case; tactical backpack |
| Displays | Laptop 14"; Tablet 11" | Laptop 14"; Tablet 11" |
| Software features | Xsight filter; Stitching; Subtraction; Summation | Xsight filter; Stitching; Subtraction; Summation |
| Accessories | Robot integration; Slider; Dual Energy, & more | Robot integration; Slider; Dual Energy, & more |

All specifications subject to change

